

BOX C

BOX, C

Osobine

Konstrukcija	O-prsten
Dodatak za vrstu konstrukciju	metrički standard
Boja	BOX, siva
Temperatura min.	-30 °C
Temperatura max.	100 °C
Temperatura FPM min.	-15 °C
Temperatura FPM max.	200 °C



D x d	Menge / Quantity	D x d	Menge / Quantity
3,00 x 1,50	20	5,00 x 2,50	15
5,00 x 1,50	20	7,00 x 2,50	15
7,00 x 1,50	20	10,00 x 2,50	15
9,00 x 1,50	20	12,00 x 2,50	15
11,00 x 1,50	20	15,00 x 2,50	15
6,00 x 2,00	20	10,00 x 3,00	10
8,00 x 2,00	20	12,00 x 3,00	10
10,00 x 2,00	20	14,00 x 3,00	10
12,00 x 2,00	20	16,00 x 3,00	10
14,00 x 2,00	20	18,00 x 3,00	10
6,30 x 2,40	15	20,20 x 3,00	5
8,30 x 2,40	15	22,20 x 3,00	5
11,30 x 2,40	15	24,20 x 3,00	5
13,30 x 2,40	15	26,20 x 3,00	5
17,30 x 2,40	15	30,20 x 3,00	5

Opis

BOX C sastoji od 30 dimenzionisanih pregrada - 425 komada

Artikal

Naziv	Materijal	Pregrade
BOX C	NBR 70 Shore A	30
BOX C FPM80	FPM 80 Shore A	30
BOX C NBR90	NBR 90 Shore A	30