


Osobine

Konstrukcija	Garnitura za zaptivanje šipke
Radni pritisak	maks. do 600 bara
Brzina max.	1,0 m/s
Temperatura min.	-30 °C
Temperatura max.	110 °C
Mediji	Mineralna ulja Vodene emulzije
Montaža	na jednodelnim klipovima
Materijal	(1) Dinamička zaptivka: PA + stakleno vlakno (2) Statička zaptivka: NBR
Primena	Hidraulika



Toleranz / Tolerance		
D	d	L
H9	h9	+0,20 0



Opis

Mala potreba za prostorom
 Visoka sigurnost pri procesu ekstruzije
 jednostavna montaža bez pomoćnog alata
 veoma otporno na habanje
 mali koeficijent trenja pri naglom kretanju i kod klizanja
 dug vek trajanja

Artikal

Naziv	D (mm)	d (mm)	L (mm)
GPK 90-1	90	69,0	8,1
GPK 100-1	100	79,0	8,1
GPK 110-1	110	89,0	8,1
GPK 120-1	120	99,0	8,1
GPK 125-1	125	104,0	8,1
GPK 130-1	130	109,0	8,1
GPK 140	140	119,0	8,1
GPK 150	150	129,0	8,1
GPK 160	160	139,0	8,1
GPK 180	180	159,0	8,1
GPK 190	190	169,0	8,1
GPK 200	200	179,0	8,1