



### Osobine

<b>Konstrukcija</b>	Garnitura za zaptivanje šipke
<b>Radni pritisak</b>	maks. do 600 bara
<b>Brzina max.</b>	1,0 m/s
<b>Temperatura min.</b>	-30 °C
<b>Temperatura max.</b>	110 °C
<b>Mediji</b>	Mineralna ulja Vodene emulzije
<b>Montaža</b>	na jednodelnim klipovima
<b>Materijal</b>	(1) Dinamička zaptivka: PA + stakleno vlakino (2) Statička zaptivka: NBR
<b>Primena</b>	Hidraulika



Toleranz / Tolerance		
D	d	L
H9	h9	+0,20 0



### Opis

Mala potreba za prostorom  
 Visoka sigurnost pri procesu ekstruzije  
 jednostavna montaža bez pomoćnog alata  
 veoma otporno na habanje  
 mali koeficijent trenja pri naglom kretanju i kod klizanja  
 dug vek trajanja

### Artikal

Naziv	D (mm)	d (mm)	L (mm)
GPK 90-1	90	69,0	8,1
GPK 100-1	100	79,0	8,1
GPK 110-1	110	89,0	8,1
GPK 120-1	120	99,0	8,1
GPK 125-1	125	104,0	8,1
GPK 130-1	130	109,0	8,1
GPK 140	140	119,0	8,1
GPK 150	150	129,0	8,1
GPK 160	160	139,0	8,1
GPK 180	180	159,0	8,1
GPK 190	190	169,0	8,1
GPK 200	200	179,0	8,1