

AGRI WAS LR

Pljosnato crevo za vodu

Osobine

Oblast primene	Agrarna tehnika Industrija i građevinarstvo
Posebne karakteristike	trpi velika opterećenja usled umetaka veoma otporna na cepanje
Pogled iznutra	PVC
Umetak	tekstilni umetak
spoljni izgled	NBR sa uzdužnim zaštitnim rebrima
Boja	crna
Temperatura min.	-20 °C
Temperatura max.	100 °C
Mediji	voda Vazduh Ulje benzin



Napomena

Takođe podesno za vazduh, ulje, benzin

Artikal

Naziv	col	Unutrašnji-Ø (mm)	Debljina zida (mm)	Radni pritisak (bar)	Dužina rolne (m)
AGRI WAS 19 LR	3/4"	19	1,5	25,0	100
AGRI WAS 25 LR	1"	25	1,5	25,0	100
AGRI WAS 32 LR	1.1/4"	32	1,5	20,0	100
AGRI WAS 38 LR	1.1/2"	38	1,5	16,0	100
AGRI WAS 52 LR	2"	52	2,0	16,0	100
AGRI WAS 65 LR	2.1/2"	65	2,0	16,0	100
AGRI WAS 76 LR	3"	75	2,5	16,0	100
AGRI WAS 90 LR	3.1/2"	90	2,5	16,0	100
AGRI WAS 102 LR	4"	102	2,5	16,0	100
AGRI WAS 127 LR	5"	127	3,0	16,0	100
AGRI WAS 152 LR	6"	152	3,0	16,0	100

BD = radni pritisak