

EURO WAS BL

Pljosnato crevo za vodu

HANSA FLEX

Osobine

| | |
|-------------------------------|---|
| Oblast primene | Agrarna tehnika Građevinska industrija Rudarstvo Brodogradnja |
| Posebne karakteristike | najviša otpornost na poteznu silu i silu razdvajanja bez širenja pod dejstvom pritiska može se ravno namotati i bez međuspojeva |
| Pogled iznutra | PVC |
| Umetak | pletene umetak od poliestra |
| spoljni izgled | PVC |
| Boja | plava |
| Temperatura min. | -10 °C |
| Temperatura max. | 60 °C |
| Mediji | voda |



Artikal

| Naziv | col | Unutrašnji-Ø (mm) | BD* pri 20°C (bar) | Razorni pritisak (bar) | Dužina rolne (m) |
|-------------------|--------|----------------------|-----------------------|---------------------------|---------------------|
| EURO WAS 1 BL | 1" | 25 | 8,5 | 25,5 | 100 |
| EURO WAS 1 1/4 BL | 1.1/4" | 32 | 8,5 | 25,5 | 100 |
| EURO WAS 1 1/2 BL | 1.1/2" | 38 | 8,5 | 25,5 | 100 |
| EURO WAS 2 BL | 2" | 51 | 6,5 | 19,5 | 100 |
| EURO WAS 2 1/2 BL | 2.1/2" | 63 | 6,5 | 19,5 | 100 |
| EURO WAS 3 BL | 3" | 76 | 5,5 | 16,5 | 100 |
| EURO WAS 4 BL | 4" | 102 | 5,5 | 16,5 | 100 |
| EURO WAS 5 BL | 5" | 127 | 3,0 | 9,0 | 100 |
| EURO WAS 6 BL | 6" | 152 | 3,0 | 9,0 | 100 |
| EURO WAS 8 BL | 8" | 204 | 2,5 | 7,0 | 100 |

BD = radni pritisak