

# EURO WAS BL

Pljosnato crevo za vodu

**HANSA FLEX**

## Osobine

<b>Oblast primene</b>	Agrarna tehnika Građevinska industrija Rudarstvo Brodogradnja
<b>Posebne karakteristike</b>	najviša otpornost na poteznu silu i silu razdvajanja bez širenja pod dejstvom pritiska može se ravno namotati i bez međuspojeva
<b>Pogled iznutra</b>	PVC
<b>Umetak</b>	pletene umetak od poliestra
<b>spoljni izgled</b>	PVC
<b>Boja</b>	plava
<b>Temperatura min.</b>	-10 °C
<b>Temperatura max.</b>	60 °C
<b>Mediji</b>	voda



## Artikal

Naziv	col	Unutrašnji-Ø (mm)	BD* pri 20°C (bar)	Razorni pritisak (bar)	Dužina rolne (m)
EURO WAS 1 BL	1"	25	8,5	25,5	100
EURO WAS 1 1/4 BL	1.1/4"	32	8,5	25,5	100
EURO WAS 1 1/2 BL	1.1/2"	38	8,5	25,5	100
EURO WAS 2 BL	2"	51	6,5	19,5	100
EURO WAS 2 1/2 BL	2.1/2"	63	6,5	19,5	100
EURO WAS 3 BL	3"	76	5,5	16,5	100
EURO WAS 4 BL	4"	102	5,5	16,5	100
EURO WAS 5 BL	5"	127	3,0	9,0	100
EURO WAS 6 BL	6"	152	3,0	9,0	100
EURO WAS 8 BL	8"	204	2,5	7,0	100

BD = radni pritisak