

Osobine

| | |
|-------------------------|--|
| Oblast primene | Baštovanstvo, poljoprivreda Creva niskog pritiska za oblast industrije i građevinarstva |
| Pogled iznutra | Prirodni i sintetički guma |
| Umetak | sintetički tekstilni umetak, otporan na cepanje |
| spoljni izgled | sintetička guma, otporan na vremenske uticaje |
| Boja | crna |
| Temperatura min. | -25 °C |
| Temperatura max. | 70 °C |
| Mediji | voda Vazduh |



Artikal

| Naziv | col | Unutrašnji-Ø (mm) | Spoljni-Ø (mm) | Radni pritisak (bar) | Razorni pritisak (bar) | min. radijus savijanja (mm) | Dužina rolne (m) |
|-----------------|--------|----------------------|-------------------|-------------------------|---------------------------|--------------------------------|---------------------|
| INDU WAS 25-5 | 1" | 25,4 | 33 | 10,0 | 30 | 254 | 40 |
| INDU WAS 28-5 | - | 28,0 | 38 | 10,0 | 30 | 280 | 40 |
| INDU WAS 32-5.5 | 1.1/4" | 32,0 | 43 | 10,0 | 30 | 210 | 40 |
| INDU WAS 38-6 | 1.1/2" | 38,0 | 50 | 10,0 | 30 | 250 | 40 |
| INDU WAS 40-6.5 | - | 40,0 | 53 | 10,0 | 30 | 280 | 40 |
| INDU WAS 45-7 | 1.3/4" | 44,5 | 54 | 10,0 | 30 | 445 | 40 |
| INDU WAS 50-7 | 2" | 50,0 | 64 | 10,0 | 30 | 350 | 40 |
| INDU WAS 60-7 | - | 60,0 | 74 | 10,0 | 30 | 400 | 40 |
| INDU WAS 63-7 | 2.1/2" | 63,5 | 74 | 10,0 | 30 | 635 | 40 |
| INDU WAS 70-7 | - | 70,0 | 84 | 10,0 | 30 | 480 | 40 |
| INDU WAS 75-7 | 3" | 75,0 | 91 | 10,0 | 30 | 550 | 40 |
| INDU WAS 80-8 | - | 80,0 | 96 | 10,0 | 30 | 600 | 40 |
| INDU WAS 90-8 | - | 90,0 | 106 | 10,0 | 30 | 650 | 40 |
| INDU WAS 102-7 | 4" | 100,0 | 116 | 10,0 | 30 | 720 | 40 |
| INDU WAS 110-9 | - | 110,0 | 128 | 10,0 | 30 | 1100 | 40 |
| INDU WAS 127-9 | 5" | 127,0 | 140 | 10,0 | 30 | 1270 | 40 |
| INDU WAS 152-11 | 6" | 150,0 | 170 | 10,0 | 30 | 1200 | 40 |
| INDU WAS 203-11 | 8" | 203,2 | 222 | 10,0 | 30 | 2032 | 20 |