

WAS STRAHL

Građevinsko crevo za vodu

HANSA FLEX

Osobine

Posebne karakteristike	veoma fleksibilno i robusno LABS sredstvo za odvajanje bez masti manji otpor protoka
Pogled iznutra	EPDM unutrašnji sloj, gladak, crn, bez pora
Umetak	sintetičke niti
spoljni izgled	EPDM neosetljiv na delovanje ozona i UV zraka
Boja	crna
Temperatura min.	-40 °C
Temperatura max.	95 °C
Temperaturni opseg	Vršna temperatura do 110°C
Mediji	voda



Napomena

Radni pritisak odnosi se na sobnu temperaturu

Artikal

Naziv	col	Unutrašnji-Ø (mm)	Debljina zida (mm)	Radni pritisak (bar)	min. radijus savijanja (mm)	Dužina rolne (m)
WAS 10-3.5 STRAHL	3/8"	10	3,5	20,0	60	50
WAS 13-3 STRAHL	1/2"	13	3,0	20,0	80	40
WAS 16-3.5 STRAHL	5/8"	16	3,5	20,0	100	40
WAS 19-4 STRAHL	3/4"	19	4,0	20,0	120	40
WAS 25-4.5 STRAHL	1"	25	4,5	20,0	150	40
WAS 32-6 STRAHL	1.1/4"	32	6,0	20,0	200	50