

# PYRO WAS RT

Pljosnato crevo za vatrogasnu službu

**HANSA FLEX**

## Osobine

<b>Oblast primene</b>	Vatrogasna služba
<b>Posebne karakteristike</b>	EPDM mešavina postojana na starenje i ozon veoma elastično i fino, izuzetno dobre vrednosti prianjanja obrađeno specijalnim postupkom vulkanizacije exceptionally abrasion resistant
<b>Norma</b>	DIN 14.811 BS 6391
<b>Pogled iznutra</b>	veoma čvrsta višeslojna poliesterska vlakna, lanac 2-struko upleten, okruglo pletena
<b>Boja</b>	crvena
<b>Mediji</b>	voda



## Artikal

Naziv	col	Unutrašnji-Ø (mm)	Radni pritisak (bar)	Kontrolni pritisak (bar)	Razorni pritisak (bar)	Dužina rolne (m)
PYRO WAS 38 RT	1.1/2"	38	16,0	25	50	15 / 20 / 30
PYRO WAS 52 RT	2"	52	16,0	25	50	15 / 20 / 30
PYRO WAS 63 RT	2.1/2"	63	16,0	25	50	15 / 20 / 30
PYRO WAS 75 RT	3"	75	16,0	25	50	15 / 20 / 30