


ND 300 BL, GRN, R

Utično crevo za niski pritisak

HANSA FLEX

Osobine

Oblast primene	Konstrukcija sistema opšta primena za vazduh, vodu itd.
Pogled iznutra	NBR (nitril baza)
Umetak	pleteni umetak od tekstila
spoljni izgled	sintetička guma
Temperatura min.	-40 °C
Temperatura max.	100 °C
Mediji	voda Vazduh Hidraulična ulja (na bazi mineralnih ulja) Rastvori za zaštitu od smrzavanja



Artikal

Naziv	DN*	Veličina	col	Unutrašnji-Ø (mm)	Unutrašnji-Ø (mm)	Spoljni-Ø (mm)	Radni pritisak (bar)	Razorni pritisak (bar)	min. radijus savijanja (mm)	Boja
ND 306 BL	6	4	1/4"	6	6,0	11,9	21,0	84	45	plava
ND 310 BL	10	6	3/8"	10	10,0	15,9	21,0	84	75	plava
ND 313 BL	12	8	1/2"	13	13,0	19,6	21,0	84	80	plava
ND 316 BL	16	10	5/8"	16	16,0	23,9	21,0	84	115	plava
ND 320 BL	19	12	3/4"	19	19,0	26,9	21,0	84	135	plava
ND 306 GRN	6	4	1/4"	6	6,0	11,9	21,0	84	45	zelena
ND 310 GRN	10	6	3/8"	10	10,0	15,9	21,0	84	75	zelena
ND 313 GRN	12	8	1/2"	13	13,0	19,6	21,0	84	80	zelena
ND 316 GRN	16	10	5/8"	16	16,0	23,9	21,0	84	115	zelena
ND 320 GRN	19	12	3/4"	19	19,0	26,9	21,0	84	135	zelena
ND 306 R	6	4	1/4"	6	6,0	11,9	21,0	84	45	crvena
ND 310 R	10	6	3/8"	10	10,0	15,9	21,0	84	75	crvena
ND 313 R	12	8	1/2"	13	13,0	19,6	21,0	84	80	crvena
ND 316 R	16	10	5/8"	16	16,0	23,9	21,0	84	115	crvena
ND 320 R	19	12	3/4"	19	19,0	26,9	21,0	84	135	crvena

DN = nominalni prečnik, nominalna širina