


# ND 300 BL, GRN, R

Utično crevo za niski pritisak

**HANSA FLEX**

## Osobine

<b>Oblast primene</b>	Konstrukcija sistema opšta primena za vazduh, vodu itd.
<b>Pogled iznutra</b>	NBR (nitril baza)
<b>Umetak</b>	pleteni umetak od tekstila
<b>spoljni izgled</b>	sintetička guma
<b>Temperatura min.</b>	-40 °C
<b>Temperatura max.</b>	100 °C
<b>Mediji</b>	voda Vazduh Hidraulična ulja (na bazi mineralnih ulja) Rastvori za zaštitu od smrzavanja



## Artikal

Naziv	DN*	Veličina	col	Unutrašnji-Ø (mm)	Unutrašnji-Ø (mm)	Spoljni-Ø (mm)	Radni pritisak (bar)	Razorni pritisak (bar)	min. radijus savijanja (mm)	Boja
ND 306 BL	6	4	1/4"	6	6,0	11,9	21,0	84	45	plava
ND 310 BL	10	6	3/8"	10	10,0	15,9	21,0	84	75	plava
ND 313 BL	12	8	1/2"	13	13,0	19,6	21,0	84	80	plava
ND 316 BL	16	10	5/8"	16	16,0	23,9	21,0	84	115	plava
ND 320 BL	19	12	3/4"	19	19,0	26,9	21,0	84	135	plava
ND 306 GRN	6	4	1/4"	6	6,0	11,9	21,0	84	45	zelena
ND 310 GRN	10	6	3/8"	10	10,0	15,9	21,0	84	75	zelena
ND 313 GRN	12	8	1/2"	13	13,0	19,6	21,0	84	80	zelena
ND 316 GRN	16	10	5/8"	16	16,0	23,9	21,0	84	115	zelena
ND 320 GRN	19	12	3/4"	19	19,0	26,9	21,0	84	135	zelena
ND 306 R	6	4	1/4"	6	6,0	11,9	21,0	84	45	crvena
ND 310 R	10	6	3/8"	10	10,0	15,9	21,0	84	75	crvena
ND 313 R	12	8	1/2"	13	13,0	19,6	21,0	84	80	crvena
ND 316 R	16	10	5/8"	16	16,0	23,9	21,0	84	115	crvena
ND 320 R	19	12	3/4"	19	19,0	26,9	21,0	84	135	crvena

DN = nominalni prečnik, nominalna širina