

# PRT M HR

Perrot spojnice, uvučeni deo, spoljni navoj

**HANSA FLEX**

## Osobine

Priključak 1	Ženski element za spojnicu
Oblik zaptivke 1	Zaptivajući sa O-prstenom
Priključak 2	BSP spoljni cilindrični navoj
Materijal	čelik
Površinska zaštita	galvanizovano



## Artikal

Naziv	Radni pritisak (bar)	Dimenzija spojnice (mm)	G1
PRT M 50 HR 1.1/2	12,0	50,0	G 1.1/2" -11
PRT M 50 HR 2	12,0	50,0	G 2"
PRT M 50 HR 2.1/2	12,0	50,0	G 2.1/2" -11
PRT M 70 HR 2	12,0	70,0	G 2"
PRT M 70 HR 2.1/2	12,0	70,0	G 2.1/2" -11
PRT M 70 HR 3	12,0	70,0	G 3" -11
PRT M 89 HR 2.1/2	12,0	89,0	G 2.1/2" -11
PRT M 89 HR 3	12,0	89,0	G 3" -11
PRT M 108 HR 2.1/2	12,0	108,0	G 2.1/2" -11
PRT M 108 HR 3	12,0	108,0	G 3" -11
PRT M 108 HR 4	12,0	108,0	G 4" -11
PRT M 133 HR 2.1/2	12,0	133,0	G 2.1/2" -11
PRT M 133 HR 4	12,0	133,0	G 4" -11
PRT M 133 HR 5	12,0	133,0	G 5" -11
PRT M 159 HR 2.1/2	12,0	159,0	G 2.1/2" -11
PRT M 159 HR 4	12,0	159,0	G 4" -11
PRT M 159 HR 6	12,0	159,0	G 6" -11