

# HK PAN

Termoprekidač nivoa HK PAN

**HANSA FLEX**

## Osobine

|                                |                |
|--------------------------------|----------------|
| Radni pritisak                 | maks. 1 bara   |
| Radna temperatura max.         | 70 °C          |
| Priključak                     | G 1/2" male    |
| Radni napon                    | 24 V DC        |
| Priključak na električnu mrežu | M12x1, 8-polig |
| Vrsta zaštite                  | IP 65          |
| Materijal                      | Zaptivka: NBR  |
| Obim isporuke                  | bez utikača    |



## Opis

Kućište okretno do 350°  
Output: 2x high-side per parameter (freely programmable, NC/NO, window/hysteresis)  
Level measurement: Sensor length 35 mm, display resolution 5 mm  
Temperature measurement: -15°C to +100°C (PT100)  
Preciznost ±1 % od granične vrednosti

## Napomene u vezi porudžbine

M12-utikač sa kablom poručiti odvojeno

## Artikal

| Naziv         | L<br>(mm) | Težina<br>(kg) |
|---------------|-----------|----------------|
| HK PAN 1 1001 | 250       | 1,0            |
| HK PAN 1 1002 | 370       | 1,0            |
| HK PAN 1 1003 | 520       | 1,0            |

## Pribor

HK PAN M Utikač M12 8-polni sa kablom