

# FI ND E MA

Element filtra za filter niskog pritiska MA

**HANSA FLEX**

## Osobine

Temperatura min. -25 °C

Temperatura max. 120 °C

Materijal Zaptivka: NBR

Radni pritisak maks. 10 bara



## Artikal

Naziv	Filterska jedinica (µm)	Površina filtera (cm <sup>2</sup> )	Qmax (L/min)	Filter material	L (mm)	Ø A (mm)	Ø B (mm)	Težina (kg)
FI ND E MA 0093 A03	3,0	590	15	neorganski	93,0	47,0	25,5	0,20
FI ND E MA 0030 P25	25,0	1824	80	organic	178,0	58,0	32,2	0,27
FI ND E MA 0025 M60	60,0	1575	150	Žičano pletivo	142,0	83,2	47,5	0,52
FI ND E MA 0050 A03	3,0	4020	200	neorganski	249,0	78,5	40,3	0,72
FI ND E MA 0050 A06	6,0	4020	200	neorganski	249,0	78,5	40,3	0,72
FI ND E MA 0050 A10	10,0	4020	200	neorganski	249,0	78,5	40,3	0,72
FI ND E MA 0060 M100	100,0	4280	300	Žičano pletivo	265,5	83,2	47,5	0,98
FI ND E MA 0040 M60	60,0	2000	330	Žičano pletivo	210,0	140,0	51,0	0,79
FI ND E MA 0045 P03	3,0	10000	350	organic	221,5	152,0	88,0	0,60
FI ND E MA 0100 M40	40,0	6370	450	Žičano pletivo	372,0	83,2	47,5	0,98
FI ND E MA 0100 M60	60,0	4410	450	Žičano pletivo	372,0	83,2	47,5	1,42
FI ND E MA 0463 A03	3,0	10650	350	neorganski	463,0	106,0	72,0	0,95
FI ND E MA 0463 A06	6,0	10650	400	neorganski	463,0	106,0	72,0	0,95
FI ND E MA 0463 A10	10,0	10650	450	neorganski	463,0	106,0	72,0	0,95

Qmax - maks. volumen protoka – Filter FI ND E MA 0050 \*\*\* za sistem sporednog filterskog voda NSFA tip D – Filter FI ND E MA 0463 \*\*\* za sistem sporednog filterskog voda NSFA tip E

## je rezervni deo za sledeće proizvode

NSFA Typ D Sistem sporednog filterskog voda, tip D

NSFA Typ E Sistem sporednog filterskog voda, tip E