

# TUE LF PN16

SLOBODNA prirubnica, sa ozubljenim nastavcima, PN10/16, čelik VZ

**HANSA FLEX**

## Osobine

|                  |  |
|------------------|--|
| Priključak 1     | Slobodna prirubnica na stepenu pritiska PN16 |
| Konstrukcija     | pravo  |
| Oblik zaptivke 1 | ravno zaptivanje                             |
| Oblast primene   | Industrija                                   |
| Norma            | DIN EN 1092-1                                |



## Artikal

| Naziv           | DN* | Veličina | col    | Ø D (mm) | K (mm) | Ø d2 (mm) | N (mm) |
|-----------------|-----|----------|--------|----------|--------|-----------|--------|
| TUE 20 LF PN16  | 20  | 12       | 3/4"   | 105,0    | 75     | 14        | 4      |
| TUE 25 LF PN16  | 25  | 16       | 1"     | 115,0    | 85     | 14        | 4      |
| TUE 32 LF PN16  | 32  | 20       | 1.1/4" | 140,0    | 100    | 18        | 4      |
| TUE 38 LF PN16  | 40  | 24       | 1.1/2" | 150,0    | 110    | 18        | 4      |
| TUE 50 LF PN16  | 50  | 32       | 2"     | 165,0    | 125    | 18        | 4      |
| TUE 63 LF PN16  | 63  | 40       | 2.1/2" | 185,0    | 145    | 18        | 4      |
| TUE 75 LF PN16  | 75  | 50       | 3"     | 200,0    | 160    | 18        | 8      |
| TUE 102 LF PN16 | 100 | 64       | 4"     | 220,0    | 180    | 18        | 8      |

N = broj rupa

## Pribor

|           |   |
|-----------|---|
| KS AL     | Stezna čaura, aluminijum                    |
| KS FIX AL | Stezna čaura za spajanje čivija, aluminijum |

## Dodatni elementi

|          |                |
|----------|----------------|
| FD C4400 | Ravna zaptivka |
|----------|----------------|