


# K-PVDF-SCHLAUCH NATUR

PVDF tubing nature

**HANSA FLEX**

## Osobine

|                  |                                     |
|------------------|-------------------------------------|
| Primena          | resistant to a variety of chemicals |
| Pogled iznutra   | PVDF                                |
| spoljni izgled   | PVDF                                |
| Boja             | Natural                             |
| Temperatura min. | -40 °C                              |
| Temperatura max. | 150 °C                              |



## Dodatne informacije

- very good temperature resistance
- extremely high pressure resistance
- sterilisable
- non-combustible (to UL 94 V-O)
- very good UV resistance
- very low gas permeability
- excellent mechanical properties

## Artikal

| Naziv          | Unutrašnji-Ø<br>(mm) | Spoljni-Ø<br>(mm) | Debljina zida<br>(mm) | min. radijus savijanja<br>(mm) | Dužina rolne<br>(m) |
|----------------|----------------------|-------------------|-----------------------|--------------------------------|---------------------|
| K- 07 10 13 16 | 2,0                  | 4,0               | 1,0                   | 60                             | 100                 |
| K- 07 10 13 17 | 4,0                  | 6,0               | 1,0                   | 75                             | 100                 |
| K- 07 10 13 18 | 6,0                  | 8,0               | 1,0                   | 85                             | 100                 |
| K- 07 10 13 19 | 8,0                  | 10,0              | 1,0                   | 100                            | 100                 |
| K- 07 10 13 20 | 10,0                 | 12,0              | 1,0                   | 125                            | 100                 |