

K-BIMETALLTHERMOMETER 46

Bimetallic thermometers

HANSA FLEX

Osobine

Tip	46
Korekcija prikaza	On end of stem
Radni pritisak	Max. 6 bar (on thermowell)
Zaštitna cev	Clamped (removable), copper alloy
Kućište	Plastic
Okno za kontrolu	Plexiglass



Napomena

Ostali podaci na upit.

Opis

Applications: Heating, plumbing, universal.

Artikal

Naziv	Područja prikazivanja	Ø (mm)	Dužina potapajućeg vratila	Navoj
K- 07 20 09 86	0 °C to +60 °C	63,0	40 mm	G 1/2
K- 07 20 09 87	0 °C to +120 °C	63,0	40 mm	G 1/2
K- 07 20 09 88	0 °C to +60 °C	63,0	60 mm	G 1/2
K- 07 20 09 89	0 °C to +120 °C	63,0	60 mm	G 1/2
K- 07 20 09 90	0 °C to +60 °C	63,0	100 mm	G 1/2
K- 07 20 09 91	0 °C to +120 °C	63,0	100 mm	G 1/2
K- 07 20 10 19	0 °C to +60 °C	80,0	40 mm	G 1/2
K- 07 20 10 20	0 °C to +120 °C	80,0	40 mm	G 1/2
K- 07 20 10 21	0 °C to +60 °C	80,0	60 mm	G 1/2
K- 07 20 10 22	0 °C to +120 °C	80,0	60 mm	G 1/2
K- 07 20 10 23	0 °C to +60 °C	80,0	100 mm	G 1/2
K- 07 20 10 24	0 °C to +120 °C	80,0	100 mm	G 1/2