

K-GMM KUNSTOFF UNTEN

Manometar za glicerina, radijalni priključak dole

Osobine

| | |
|---|--|
| Tip | 113.13 |
| Verzija | Burdon-ov manometar sa glicerinskim punjenjem |
| Primena | For gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise |
| Klasa kvaliteta | 2,5 |
| Temperatura medija | maks. +60 °C |
| Temperatura okoline | -20 °C do +60 °C |
| Kućište | Plastika, crna |
| Materijal impulsnog davača i mehanizma pokazivača | Bakarna legura |
| Okno za kontrolu | PMMA, sa zavarenim kućištem |



Napomena

Ostali podaci na upit.

Opis

Za merna mesta sa visokim dinamičnim opterećenjima pritiska i vibracijama

Artikal

| Naziv | Merni opseg | Ø (mm) | Priključak |
|----------------|---------------|--------|------------|
| K- 07 20 07 55 | -1 / +0.6 bar | 63,0 | G 1/4" |
| K- 07 20 07 56 | -1 / +1.5 bar | 63,0 | G 1/4" |
| K- 07 20 07 57 | -1 / +3.0 bar | 63,0 | G 1/4" |
| K- 07 20 07 58 | -1 / +5.0 bar | 63,0 | G 1/4" |
| K- 07 20 07 59 | -1 / +9.0 bar | 63,0 | G 1/4" |
| K- 07 20 07 60 | -1 / 0.0 bar | 63,0 | G 1/4" |
| K- 07 20 07 61 | 0 - 1.0 bar | 63,0 | G 1/4" |
| K- 07 20 07 62 | 0 - 1.6 bar | 63,0 | G 1/4" |
| K- 07 20 07 63 | 0 - 2.5 bar | 63,0 | G 1/4" |