

# K-DIFFERENZDRUCKMANO Z

Differential pressure gauges with parallel male connector

**HANSA FLEX**

## Osobine

Tip	711.12
Verzija	Bourdon-tube pressure gauge with parallel male connector and two separate measuring systems
Primena	to measure differential pressures or two different pressures For gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise
Klasa kvaliteta	1,6
Temperatura medija	maks. +60 °C
Temperatura okoline	-20 °C do +60 °C
Kućište, prsten	Steel, black
Materijal impulsnog davača i mehanizma pokazivača	Bakarna legura
Okno za kontrolu	Flat instrument glass



## Napomena

Ostali podaci na upit.

## Artikal

Naziv	Merni opseg	Ø (mm)	Priključak
K- 07 20 00 55	0 - 1.0 bar	100,0	G 1/2"
K- 07 20 00 56	0 - 1.6 bar	100,0	G 1/2"
K- 07 20 00 57	0 - 2.5 bar	100,0	G 1/2"
K- 07 20 00 58	0 - 4.0 bar	100,0	G 1/2"
K- 07 20 00 59	0 - 6.0 bar	100,0	G 1/2"
K- 07 20 00 60	0 - 10.0 bar	100,0	G 1/2"