

K-KFMM U MBAR

Capsule-type pressure gauges, connection radial on bottom

HANSA FLEX

Osobine

Tip	611.10 (Ø 63), 612.20 (Ø 100)
Verzija	Capsule-type pressure gauge
Primena	For gaseous, dry, non-corrosive media
Klasa kvaliteta	1,6
Temperatura medija	max. +100 °C
Temperatura okoline	-20 °C do +60 °C
Kućište	Steel, black (Ø 63 mm)CrNi steel (Ø 100 mm)
Materijal impulsnog davača i mehanizma pokazivača	Bakarna legura
Okno za kontrolu	Plexiglass (Ø 63 mm), flat instrument glass (Ø 100 mm)



Napomena

Ostali podaci na upit.

Opis

With zero correction

Artikal

Naziv	Merni opseg	Ø (mm)	Priključak
K- 07 20 06 88	-160 / 0 mbar	63,0	G 1/4"
K- 07 20 06 89	-100 / 0 mbar	63,0	G 1/4"
K- 07 20 06 90	-60 / 0 mbar	63,0	G 1/4"
K- 07 20 06 91	0 - 40 mbar	63,0	G 1/4"
K- 07 20 06 92	0 - 60 mbar	63,0	G 1/4"
K- 07 20 06 93	0 - 100 mbar	63,0	G 1/4"
K- 07 20 06 94	0 - 160 mbar	63,0	G 1/4"
K- 07 20 06 95	0 - 250 mbar	63,0	G 1/4"
K- 07 20 06 96	0 - 400 mbar	63,0	G 1/4"
K- 07 20 01 13	-160 / 0 mbar	100,0	G 1/2"
K- 07 20 01 14	-100 / 0 mbar	100,0	G 1/2"
K- 07 20 01 15	-60 / 0 mbar	100,0	G 1/2"
K- 07 20 01 16	-25 / +15 mbar	100,0	G 1/2"
K- 07 20 01 17	-40 / +20 mbar	100,0	G 1/2"
K- 07 20 01 18	0 - 25 mbar	100,0	G 1/2"
K- 07 20 01 19	0 - 40 mbar	100,0	G 1/2"
K- 07 20 01 20	0 - 60 mbar	100,0	G 1/2"
K- 07 20 01 21	0 - 100 mbar	100,0	G 1/2"
K- 07 20 01 22	0 - 160 mbar	100,0	G 1/2"
K- 07 20 01 23	0 - 250 mbar	100,0	G 1/2"
K- 07 20 01 24	0 - 400 mbar	100,0	G 1/2"