

K-MANO U

Pressure gauges (CrNi steel type / connection radial on bottom)

HANSA FLEX

Osobine

| | |
|---------------------|--|
| Tip | 232.50 |
| Verzija | Bourdon-tube pressure gauge, CrNi steel type, all-stainless steel |
| Primena | For gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise |
| Klasa kvaliteta | 1.6 (Ø 63 mm), 1.0 (Ø 100 mm and Ø 160 mm) |
| Temperatura medija | max. +200 °C |
| Temperatura okoline | -40 °C to +60 °C |
| Kućište | CrNi steel |
| Okno za kontrolu | Laminated safety glass Ø 63 = Polycarbonate |



Napomena

Ostali podaci na upit.

Artikal

| Naziv | Merni opseg | Ø (mm) | Priključak |
|----------------|----------------|--------|------------|
| K- 07 20 06 01 | -1 / 0.0 bar | 63,0 | G 1/4" |
| K- 07 20 06 02 | 0 - 2.5 bar | 63,0 | G 1/4" |
| K- 07 20 06 03 | 0 - 4.0 bar | 63,0 | G 1/4" |
| K- 07 20 06 04 | 0 - 6.0 bar | 63,0 | G 1/4" |
| K- 07 20 06 05 | 0 - 10.0 bar | 63,0 | G 1/4" |
| K- 07 20 06 06 | 0 - 16.0 bar | 63,0 | G 1/4" |
| K- 07 20 06 07 | 0 - 25.0 bar | 63,0 | G 1/4" |
| K- 07 20 06 08 | 0 - 40.0 bar | 63,0 | G 1/4" |
| K- 07 20 06 09 | 0 - 100.0 bar | 63,0 | G 1/4" |
| K- 07 20 00 36 | -1 / 0.0 bar | 100,0 | G 1/2" |
| K- 07 20 00 37 | -1 / +0.6 bar | 100,0 | G 1/2" |
| K- 07 20 00 38 | -1 / +1.5 bar | 100,0 | G 1/2" |
| K- 07 20 00 39 | -1 / +3.0 bar | 100,0 | G 1/2" |
| K- 07 20 00 40 | -1 / +5.0 bar | 100,0 | G 1/2" |
| K- 07 20 00 41 | -1 / +9.0 bar | 100,0 | G 1/2" |
| K- 07 20 00 42 | -1 / +15.0 bar | 100,0 | G 1/2" |
| K- 07 20 00 43 | 0 - 1.0 bar | 100,0 | G 1/2" |
| K- 07 20 00 44 | 0 - 1.6 bar | 100,0 | G 1/2" |
| K- 07 20 00 45 | 0 - 2.5 bar | 100,0 | G 1/2" |
| K- 07 20 00 46 | 0 - 4.0 bar | 100,0 | G 1/2" |
| K- 07 20 00 47 | 0 - 6.0 bar | 100,0 | G 1/2" |
| K- 07 20 00 48 | 0 - 10.0 bar | 100,0 | G 1/2" |
| K- 07 20 00 49 | 0 - 16.0 bar | 100,0 | G 1/2" |
| K- 07 20 00 50 | 0 - 25.0 bar | 100,0 | G 1/2" |
| K- 07 20 00 51 | 0 - 40.0 bar | 100,0 | G 1/2" |
| K- 07 20 00 52 | 0 - 60.0 bar | 100,0 | G 1/2" |
| K- 07 20 03 10 | -1 / 0.0 bar | 160,0 | G 1/2" |
| K- 07 20 03 11 | -1 / +0.6 bar | 160,0 | G 1/2" |
| K- 07 20 03 12 | 0 - 1.0 bar | 160,0 | G 1/2" |
| K- 07 20 03 13 | 0 - 10.0 bar | 160,0 | G 1/2" |
| K- 07 20 03 14 | 0 - 16.0 bar | 160,0 | G 1/2" |
| K- 07 20 03 15 | 0 - 25.0 bar | 160,0 | G 1/2" |