

# K-MANO 1

Pressure gauges (CrNi steel type / safety housing)

**HANSA FLEX**

## Osobine

Tip	232.30
Verzija	Bourdon-tube pressure gauge, CrNi steel type, with solid baffle wall and blow-out (safety housing)
Primena	For gaseous or liquid, corrosive and crystallising media which do not have high viscosity, also in corrosive atmosphere
Klasa kvaliteta	1,6 (Ø 63 mm), 1,0 (Ø 100 mm)
Temperatura medija	max. +200 °C
Temperatura okoline	-40 °C to +60 °C
Kućište	CrNi steel
Okno za kontrolu	Laminated safety glass Ø 63 = Polycarbonate



## Napomena

Ostali podaci na upit.

## Opis

Safety version with more fracture-resistant separating wall

## Artikal

Naziv	Merni opseg	Ø (mm)	Priključak
K- 07 20 07 15	-1 / 0.0 bar	63,0	G 1/4"
K- 07 20 07 16	0 - 1.6 bar	63,0	G 1/4"
K- 07 20 07 17	0 - 2.5 bar	63,0	G 1/4"
K- 07 20 07 18	0 - 4.0 bar	63,0	G 1/4"
K- 07 20 07 19	0 - 6.0 bar	63,0	G 1/4"
K- 07 20 07 20	0 - 10.0 bar	63,0	G 1/4"
K- 07 20 07 21	0 - 16.0 bar	63,0	G 1/4"
K- 07 20 07 22	0 - 25.0 bar	63,0	G 1/4"
K- 07 20 07 23	0 - 40.0 bar	63,0	G 1/4"
K- 07 20 07 24	0 - 60.0 bar	63,0	G 1/4"
K- 07 20 07 25	0 - 100.0 bar	63,0	G 1/4"
K- 07 20 01 97	0 - 1.0 bar	100,0	G 1/2"
K- 07 20 01 98	0 - 1.6 bar	100,0	G 1/2"
K- 07 20 01 99	0 - 2.5 bar	100,0	G 1/2"
K- 07 20 02 00	0 - 4.0 bar	100,0	G 1/2"
K- 07 20 02 01	0 - 6.0 bar	100,0	G 1/2"
K- 07 20 02 02	0 - 10.0 bar	100,0	G 1/2"
K- 07 20 02 03	0 - 16.0 bar	100,0	G 1/2"
K- 07 20 02 04	0 - 25.0 bar	100,0	G 1/2"
K- 07 20 02 05	0 - 40.0 bar	100,0	G 1/2"
K- 07 20 02 06	0 - 60.0 bar	100,0	G 1/2"
K- 07 20 02 07	0 - 100.0 bar	100,0	G 1/2"
K- 07 20 02 08	0 - 160.0 bar	100,0	G 1/2"
K- 07 20 02 09	0 - 250.0 bar	100,0	G 1/2"
K- 07 20 02 10	0 - 400.0 bar	100,0	G 1/2"