# K-PRMM ROB U

Robust diaphragm pressure gauges, connection radial on bottom

## Osobine

| | |
|---|---|
| **Tip** | 422.12 (robust), 432.50 (chemical) |
| **Verzija** | Diaphragm pressure gauge in robust design or for chemical applications |
| **Primena** | at chemical applications in aggressive environments<br>for gaseous or liquid media, |
| **Klasa kvaliteta** | 1,6 |
| **Temperatura medija** | max. +100 °C |
| **Temperatura okoline** | -20 °C do +60 °C |
| **Ø merne prirubnice** | 100 mm |
| **Kućište, prsten** | Grey cast iron / CrNi steel, black (robust type), CrNi steel (type for chemical applications) |
| **Impulsni davač** | CrNi steel |
| **Okno za kontrolu** | Flat instrument glass (robust type), Laminated safety glass (type for chemical applications) |
| **Mehanizam pokazivača** | Copper alloy (robust type), CrNi steel (type for chemical applications) |




## Napomena

Ostali podaci na upit.

## Artikal

| Naziv | Merni opseg | Ø (mm) | Priključak |
|---|---|---|---|
| **K- 07 20 10 99** | -1 / +1.5 bar | 100,0 | G 1/2" |
| **K- 07 20 11 00** | 0 - 1.0 bar | 100,0 | G 1/2" |
| **K- 07 20 11 01** | 0 - 1.6 bar | 100,0 | G 1/2" |
| **K- 07 20 11 02** | 0 - 2.5 bar | 100,0 | G 1/2" |
| **K- 07 20 11 03** | 0 - 4.0 bar | 100,0 | G 1/2" |
| **K- 07 20 11 04** | 0 - 6.0 bar | 100,0 | G 1/2" |
| **K- 07 20 11 05** | 0 - 10.0 bar | 100,0 | G 1/2" |
| **K- 07 20 11 06** | 0 - 16.0 bar | 100,0 | G 1/2" |
| **K- 07 20 11 07** | 0 - 25.0 bar | 100,0 | G 1/2" |

*Uprkos pažljivom proveravanju, ne možemo isključiti greške i ne preuzimamo nikakvu garanciju za navedene podatke.*