

K-PRMM CHEMIE U

Diaphragm pressure gauges for chemical applications, connection radial on bottom

HANSA FLEX

Osobine

| | |
|----------------------|---|
| Tip | 422.12 (robust), 432.50 (chemical) |
| Verzija | Diaphragm pressure gauge in robust design or for chemical applications |
| Primena | at chemical applications in aggressive environments for gaseous or liquid media, |
| Klasa kvaliteta | 1,6 |
| Temperatura medija | max. +100 °C |
| Temperatura okoline | -20 °C do +60 °C |
| Ø merne prirubnice | 100 mm |
| Kućište, prsten | Grey cast iron / CrNi steel, black (robust type), CrNi steel (type for chemical applications) |
| Impulsni davač | CrNi steel |
| Okno za kontrolu | Flat instrument glass (robust type), Laminated safety glass (type for chemical applications) |
| Mehanizam pokazivača | Copper alloy (robust type), CrNi steel (type for chemical applications) |



Napomena

Ostali podaci na upit.

Artikal

| Naziv | Merni opseg | Ø (mm) | Priključak |
|----------------|--------------|--------|------------|
| K- 07 20 10 25 | 0 - 6.0 bar | 100,0 | G 1/2" |
| K- 07 20 10 26 | 0 - 10.0 bar | 100,0 | G 1/2" |