K-PRMM CHEMIE U

Diaphragm pressure gauges for chemical applications, connection radial on bottom

Osobine

Tip	422.12 (robust), 432.50 (chemical)
Verzija	Diaphragm pressure gauge in robust design or for chemical applications
Primena	at chemical applications in aggressive environments for gaseous or liquid media,
Klasa kvaliteta	1,6
Temperatura medija	max. +100 °C
Temperatura okoline	-20 °C do +60 °C
Ø merne prirubnice	100 mm
Kućište, prsten	Grey cast iron / CrNi steel, black (robust type), CrNi steel (type for chemical applications)
Impulsni davač	CrNi steel
Okno za kontrolu	Flat instrument glass (robust type), Laminated safety glass (type for chemical applications)
Mehanizam pokazivača	Copper alloy (robust type), CrNi steel (type for chemical applications)



Napomena

Ostali podaci na upit.

Artikal

Naziv	Merni opseg	Ø (mm)	Priključak
K- 07 20 10 25	0 - 6.0 bar	100,0	G 1/2"
K- 07 20 10 26	0 - 10.0 bar	100,0	G 1/2"

Uprkos pažljivom proveravanju, ne možemo isključiti greške i ne preuzimamo nikakvu garanciju za navedene podatke.