

K-MANO ROB H

Robust pressure gauges, connection on rear, eccentric

HANSA FLEX

Osobine

Tip	212.20
Verzija	Robust Bourdon-tube pressure gauge
Primena	For gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise
Klasa kvaliteta	1,0
Temperatura medija	max. +80 °C
Temperatura okoline	-40 °C to +60 °C
Kućište	CrNi steel
Impulsni davač	Copper alloy (≤ 100 bar), CrNi steel (> 100 bar)
Okno za kontrolu	Flat instrument glass
Mehanizam pokazivača	Copper alloy



Napomena

Ostali podaci na upit.

Dodatne informacije

Further measuring ranges on request

Version for panel mounting available on request. Version with max. pointer available on request

Artikal

Naziv	Merni opseg	Ø (mm)	Priključak
K- 07 20 01 67	-1 / 0.0 bar	100,0	G 1/2"
K- 07 20 01 68	0 - 1.0 bar	100,0	G 1/2"
K- 07 20 01 69	0 - 1.6 bar	100,0	G 1/2"
K- 07 20 01 70	0 - 2.5 bar	100,0	G 1/2"
K- 07 20 01 71	0 - 4.0 bar	100,0	G 1/2"
K- 07 20 01 72	0 - 6.0 bar	100,0	G 1/2"
K- 07 20 01 73	0 - 10.0 bar	100,0	G 1/2"
K- 07 20 01 74	0 - 16.0 bar	100,0	G 1/2"
K- 07 20 01 75	0 - 25.0 bar	100,0	G 1/2"
K- 07 20 01 76	0 - 40.0 bar	100,0	G 1/2"
K- 07 20 01 77	0 - 160.0 bar	100,0	G 1/2"
K- 07 20 01 78	0 - 250.0 bar	100,0	G 1/2"