

Osobine

Tip	111.11
Verzija	Bourdon-tube pressure gauge acc. to EN 562
Primena	For welding systems and cutting machines or similar processes
Klasa kvaliteta	2,5
Temperatura medija	maks. +60 °C
Temperatura okoline	-40 °C to +60 °C
Kućište	Steel, brass-coloured
Materijal impulsnog davača i mehanizma pokazivača	Bakarna legura
Okno za kontrolu	Polycarbonate



Napomena

Ostali podaci na upit.

Artikal

Naziv	Merni opseg	Ø (mm)	Natpis	Priključak
K- 07 20 11 08	0 - 16.0 bar	63,0	oxygen	G 1/4
K- 07 20 11 10	0 - 315.0 bar	63,0	oxygen	G 1/4
K- 07 20 11 12	0 - 2.5 bar	63,0	acetylene	G 1/4
K- 07 20 11 13	0 - 40.0 bar	63,0	acetylene	G 1/4

je rezervni deo za sledeće proizvode

K-FLASCHENDRUCKR 200 N GASE	Regulator pritiska flaše, pritisak flaše 200 bar, za nezapaljive gasove
K-FLASCHENDRUCKR 200 GASE	Regulator pritiska flaše, pritisak flaše 200 bar, za zapaljive gasove
K-FLASCHENDRUCKR 300 N GASE	Regulator pritiska flaše, pritisak flaše 300 bar, za nezapaljive gasove
K-FLASCHENDRUCKR 300 GASE	Regulator pritiska flaše, pritisak flaše 300 bar, za zapaljive gasove