

K-RMM HFR STAHLBLECH CR

Standard pressure gauges with chrome-plated sheet-steel bezel, connection on rear

HANSA FLEX

Osobine

Tip	111.12
Verzija	Bourdon-tube pressure gauge, standard design, mounting ring
Primena	gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise
Klasa kvaliteta	1,6
Temperatura medija	maks. +60 °C
Temperatura okoline	-20 °C do +60 °C
Kućište	Sheet steel
Materijal impulsnog davača i mehanizma pokazivača	Bakarna legura
Okno za kontrolu	Transparent plastic



Napomena

Ostali podaci na upit.

Artikal

Naziv	Merni opseg	Ø (mm)	Priključak
K- 07 20 04 37	-1 / 0.0 bar	40,0	G 1/8
K- 07 20 04 38	0 - 1.0 bar	40,0	G 1/8
K- 07 20 04 39	0 - 1.6 bar	40,0	G 1/8
K- 07 20 04 40	0 - 2.5 bar	40,0	G 1/8
K- 07 20 04 41	0 - 4.0 bar	40,0	G 1/8
K- 07 20 04 42	0 - 6.0 bar	40,0	G 1/8
K- 07 20 04 43	0 - 10.0 bar	40,0	G 1/8
K- 07 20 04 44	0 - 16.0 bar	40,0	G 1/8
K- 07 20 04 45	0 - 25.0 bar	40,0	G 1/8
K- 07 20 04 46	0 - 40.0 bar	40,0	G 1/8
K- 07 20 05 41	-1 / 0.0 bar	50,0	G 1/4
K- 07 20 05 42	0 - 1.0 bar	50,0	G 1/4
K- 07 20 05 43	0 - 1.6 bar	50,0	G 1/4
K- 07 20 05 44	0 - 2.5 bar	50,0	G 1/4
K- 07 20 05 45	0 - 4.0 bar	50,0	G 1/4
K- 07 20 05 46	0 - 6.0 bar	50,0	G 1/4
K- 07 20 05 47	0 - 10.0 bar	50,0	G 1/4
K- 07 20 05 48	0 - 16.0 bar	50,0	G 1/4
K- 07 20 05 49	0 - 25.0 bar	50,0	G 1/4
K- 07 20 05 50	0 - 40.0 bar	50,0	G 1/4