K-TR PA 612

Plastic pipes made of polyamide PA 12 (10 pcs.)

HANSA-FLEX

Osobine

Radna temperatura	-60 °C to +100 °C (PA 12)
Osobine	Resistant to corrosion, vibration, impact, ageing, high pressures and heat
Dužina cevi	3 m
Jedinica pakovanja	10 lengths (O.D. 28 mm in packs of 5 lengths), only sold in complete packaging units!
Materijal	Polyamid PA 12, hard (according to DIN 73378)



Napomena

Operating pressure with 2.5 x overpressure safety!
Ostali podaci na upit.

Opis

Push-in fittings - aluminium pipes - plastic pipes - take-off points. The flexible, maintenance-free compressed air installation system from compressor to take-off point. For Ø 12 mm to Ø 32 mm pipe systems and for Ø 4 mm to Ø 12 mm pneumatic applications

Artikal

Naziv	Cev spolja Ø (mm)	Cev unutrašnji Ø (mm)	maks. radni pritisak pri 20°C (bar)	Boja
K- 07 10 04 57	12	9	38	plava
K- 07 10 04 59	12	9	38	crna
K- 07 10 04 61	15	12	25	plava
K- 07 10 04 63	15	12	25	crna
K- 07 10 04 65	18	14	28	plava
K- 07 10 04 67	18	14	28	crna
K- 07 10 04 69	22	18	22	plava
K- 07 10 04 71	22	18	22	crna
K- 07 10 04 73	28	23	20	plava
K- 07 10 04 75	28	23	20	crna

Uprkos pažljivom proveravanju, ne možemo isključiti greške i ne preuzimamo nikakvu garanciju za navedene podatke.