

K-TR PA 12

Plastic pipes made of polyamide PA 12 (20 pcs.)

HANSA FLEX

Osobine

| | |
|--------------------|--|
| Radna temperatura | -60 °C to +100 °C (PA 12) |
| Osobine | Resistant to corrosion, vibration, impact, ageing, high pressures and heat |
| Dužina cevi | 3 m |
| Jedinica pakovanja | 20 lengths (O.D. 28 mm in packs of 10 lengths), only sold in complete packaging units! |
| Materijal | Polyamid PA 12, hard (according to DIN 73378) |



Napomena

Operating pressure with 2.5 x overpressure safety!

Ostali podaci na upit.

Opis

Push-in fittings - aluminium pipes - plastic pipes - take-off points. The flexible, maintenance-free compressed air installation system from compressor to take-off point. For Ø 12 mm to Ø 32 mm pipe systems and for Ø 4 mm to Ø 12 mm pneumatic applications

Artikal

| Naziv | Cev spolja Ø (mm) | Cev unutrašnji Ø (mm) | maks. radni pritisak pri 20°C (bar) | Boja |
|----------------|----------------------|--------------------------|--|-------|
| K- 07 10 04 56 | 12 | 9 | 38 | plava |
| K- 07 10 04 58 | 12 | 9 | 38 | crna |
| K- 07 10 04 60 | 15 | 12 | 25 | plava |
| K- 07 10 04 62 | 15 | 12 | 25 | crna |
| K- 07 10 04 64 | 18 | 14 | 28 | plava |
| K- 07 10 04 66 | 18 | 14 | 28 | crna |
| K- 07 10 04 68 | 22 | 18 | 22 | plava |
| K- 07 10 04 70 | 22 | 18 | 22 | crna |
| K- 07 10 04 72 | 28 | 23 | 20 | plava |
| K- 07 10 04 74 | 28 | 23 | 20 | crna |