

K-TR PA 12

Plastic pipes made of polyamide PA 12 (20 pcs.)

HANSA FLEX

Osobine

Radna temperatura	-60 °C to +100 °C (PA 12)
Osobine	Resistant to corrosion, vibration, impact, ageing, high pressures and heat
Dužina cevi	3 m
Jedinica pakovanja	20 lengths (O.D. 28 mm in packs of 10 lengths), only sold in complete packaging units!
Materijal	Polyamid PA 12, hard (according to DIN 73378)



Napomena

Operating pressure with 2.5 x overpressure safety!

Ostali podaci na upit.

Opis

Push-in fittings - aluminium pipes - plastic pipes - take-off points. The flexible, maintenance-free compressed air installation system from compressor to take-off point. For Ø 12 mm to Ø 32 mm pipe systems and for Ø 4 mm to Ø 12 mm pneumatic applications

Artikal

Naziv	Cev spolja Ø (mm)	Cev unutrašnji Ø (mm)	maks. radni pritisak pri 20°C (bar)	Boja
K- 07 10 04 56	12	9	38	plava
K- 07 10 04 58	12	9	38	crna
K- 07 10 04 60	15	12	25	plava
K- 07 10 04 62	15	12	25	crna
K- 07 10 04 64	18	14	28	plava
K- 07 10 04 66	18	14	28	crna
K- 07 10 04 68	22	18	22	plava
K- 07 10 04 70	22	18	22	crna
K- 07 10 04 72	28	23	20	plava
K- 07 10 04 74	28	23	20	crna