

# K-SPIR SCHL DREH VERSCHRAU V

Spiral hose, with swivel adapter and kink protector, braided

**HANSA FLEX**

## Osobine

Vrsta priključka with kink protector, swivel type

Radna temperatura -40 °C to +74 °C



## Napomena

Ostali podaci na upit.

## Opis

Standard type or with braided reinforcements for high pressures. These exceptionally elastic polyurethane hoses boast a recoil force similar to that of conventional nylon spiral hose, but with less tendency to loop and significantly better resistance to abrasion. There is consequently less danger of scratching coated or sensitive surfaces. The hose is extremely flexible and non-kinking.

## Artikal

Naziv	Navoj	Ø creva unutra (mm)	Ø creva spolja (mm)	Ø spoljnog navoja (mm)	Max. working pressure resistance at 23°C (bar)	maks. radna dužina (m)
K- 07 10 07 43	G 1/4	6,3	9,5	42	14	3,0
K- 07 10 07 44	G 1/4	6,3	9,5	42	14	6,0
K- 07 10 07 45	G 1/4	6,3	9,5	42	14	7,5
K- 07 10 07 46	G 3/8	8,0	12,0	55	14	3,0
K- 07 10 07 47	G 3/8	8,0	12,0	55	14	6,0
K- 07 10 07 48	G 3/8	8,0	12,0	55	14	7,5

## Pribor

K-DREHBARE VERSCHRAUBUNG Swivel adapters