

# K-HYDR-KUPPLUNG IG MS

Hydraulic couplings, brass

**HANSA FLEX**

## Osobine

|                                  |   |
|----------------------------------|---|
| Radni pritisak                   | See table. All values referred to a medium temperature of 50 °C (static working pressure)   |
| Protok vazduha                   | 440 l/min (G 1/8), 840 l/min (G 1/4), 1.280 l/min (G 3/8), 1.950 l/min (G 1/2), 4.500 l/min (G 3/4) (at 6 bar and $\Delta p = 0,5$ bar) |
| Temperatura medija               | -20 °C to +100 °C   |
| Kućište, čaura, ventil           | Brass   |
| Opruga, sigurnosni prsten, kugle | stain less steel  |
| Zaptivni materijal               | NBR   |



## Napomena

Ostali podaci na upit.

## Opis

Hydraulic couplings, both sides sealing, for liquid media acc. to ISO 7241, B Series.

## Artikal

| Naziv          | Priključak   | NW   | Radni pritisak (bar) | Dužina (mm) | SW (mm) |
|----------------|--------------|------|----------------------|-------------|---------|
| K- 07 35 03 81 | G 1/8 female | 4,3  | 250,0                | 48,5        | 14      |
| K- 07 35 03 82 | G 1/4 female | 6,3  | 200,0                | 57,6        | 19      |
| K- 07 35 03 83 | G 3/8 female | 7,5  | 200,0                | 64,2        | 22      |
| K- 07 35 03 84 | G 1/2 female | 11,0 | 150,0                | 76,0        | 27      |
| K- 07 35 03 85 | G 3/4 female | 13,0 | 100,0                | 96,0        | 34      |