

K-HYDR-KUPPLUNG IG POM

Hydraulic couplings, POM

HANSA FLEX

Osobine

Radni pritisak	See table. All values referred to a medium temperature of 50 °C (static working pressure)
Protok vazduha	440 l/min (G 1/8), 840 l/min (G 1/4), 1.280 l/min (G 3/8), 1.950 l/min (G 1/2), 4.500 l/min (G 3/4) (at 6 bar and $\Delta p = 0,5$ bar)
Temperatura medija	-20 °C to +90 °C
Kućište, čaura	POM (Delrin), white
Ventil	Stainless steel 1.4305
Opruga, sigurnosni prsten, kugle	stain less steel
Zaptivni materijal	NBR



Napomena

Ostali podaci na upit.

Opis

Hydraulic couplings, both sides sealing, for liquid media acc. to ISO 7241, B Series.

Artikal

Naziv	Priključak	Radni pritisak (bar)	Dužina (mm)	NW	SW (mm)
K- 07 35 03 76	G 1/8 female	15,0	48,5	4,3	14
K- 07 35 03 77	G 1/4 female	15,0	57,6	6,0	19
K- 07 35 03 78	G 3/8 female	15,0	64,2	7,5	22
K- 07 35 03 79	G 1/2 female	10,0	76,0	11,0	27
K- 07 35 03 80	G 3/4 female	10,0	96,0	13,0	34