
K-LKM 5 UWB

Non-interchangeable quick disconnect couplings DN 5

Osobine

Radni pritisak	0 - 35 bar, maximum static working pressure (non-pulsating)
Protok vazduha	560 l/min (at 6 bar and Δp = 0.5 bar)
Temperatura medija	-20 °C to +100 °C
Čaura za odbravljivanje	Anodised aluminium
Opruga, sigurnosni prsten, kugle	stain less steel
Zaptivni materijal	NBR



Napomena

Standard push-in plugs for couplings DN 5 and DN 7.2 – DN 7.8 are compatible with these non-interchangeable couplings.
Ostali podaci na upit.

Opis

One-hand quick disconnect couplings with a large bore. Different media can be connected safely and non-interchangeably even when space is restricted, thanks to the colour-coded coupling and plug and the different coupling profiles defined for each of the four colours. Only couplings and plugs of the same colour fit together.

Artikal

Naziv	Priključak	Boja	Dužina (mm)	SW (mm)
K- 07 35 06 80	G 1/8 male	zelena	45,0	14
K- 07 35 06 81	G 1/4 male	zelena	47,0	17
K- 07 35 06 82	G 1/8 female	zelena	45,0	14
K- 07 35 06 83	G 1/4 female	zelena	47,0	17
K- 07 35 06 84	G 1/8 male	Brown	45,0	14
K- 07 35 06 85	G 1/4 male	Brown	47,0	17
K- 07 35 06 86	G 1/8 female	Brown	45,0	14
K- 07 35 06 87	G 1/4 female	Brown	47,0	17
K- 07 35 06 88	G 1/8 male	plava	45,0	14
K- 07 35 06 89	G 1/4 male	plava	47,0	17
K- 07 35 06 90	G 1/8 female	plava	45,0	14
K- 07 35 06 91	G 1/4 female	plava	47,0	17
K- 07 35 06 92	G 1/8 male	crvena	45,0	14
K- 07 35 06 93	G 1/4 male	crvena	47,0	17
K- 07 35 06 94	G 1/8 female	crvena	45,0	14
K- 07 35 06 95	G 1/4 female	crvena	47,0	17

Uprkos pažljivom proveravanju, ne možemo isključiti greške i ne preuzimamo nikakvu garanciju za navedene podatke.