


# K-LKM 7,8 UWB

Non-interchangeable quick disconnect couplings DN 7.8

**HANSA FLEX**

## Osobine

|                                  |   |
|----------------------------------|---|
| Radni pritisak                   | 0 - 35 bar, maximum static working pressure (non-pulsating) |
| Protok vazduha                   | 1.800 l/min (at 6 bar and $\Delta p = 0.5$ bar)             |
| Temperatura medija               | -20 °C to +100 °C   |
| Kućište                          | Brass   |
| Ventil                           | Die-cast zinc, nickel-plated                                |
| Čaura za odbravljivanje          | Anodised aluminium  |
| Opruga, sigurnosni prsten, kugle | stain less steel  |
| Zaptivni materijal               | NBR   |



## Napomena

Standard push-in plugs for couplings DN 5 and DN 7.2 – DN 7.8 are compatible with these non-interchangeable couplings.

Ostali podaci na upit.

## Opis

One-hand quick disconnect couplings with a large bore. Different media can be connected safely and non-interchangeably even when space is restricted, thanks to the colour-coded coupling and plug and the different coupling profiles defined for each of the four colours. Only couplings and plugs of the same colour fit together.

## Artikal

| Naziv          | Priključak   | Boja   | Dužina (mm) | SW (mm) |
|----------------|--------------|--------|-------------|---------|
| K- 07 35 08 01 | G 1/4 male   | zelena | 57,5        | 19      |
| K- 07 35 08 02 | G 3/8 male   | zelena | 57,5        | 19      |
| K- 07 35 08 03 | G 1/4 female | zelena | 55,5        | 19      |
| K- 07 35 08 04 | G 3/8 female | zelena | 54,5        | 19      |
| K- 07 35 08 05 | G 1/4 male   | Brown  | 57,5        | 19      |
| K- 07 35 08 06 | G 3/8 male   | Brown  | 57,5        | 19      |
| K- 07 35 08 07 | G 1/4 female | Brown  | 55,5        | 19      |
| K- 07 35 08 08 | G 3/8 female | Brown  | 54,5        | 19      |
| K- 07 35 08 09 | G 1/4 male   | plava  | 57,5        | 19      |
| K- 07 35 08 10 | G 3/8 male   | plava  | 57,5        | 19      |
| K- 07 35 08 11 | G 1/4 female | plava  | 55,5        | 19      |
| K- 07 35 08 12 | G 3/8 female | plava  | 54,5        | 19      |
| K- 07 35 08 13 | G 1/4 male   | crvena | 57,5        | 19      |
| K- 07 35 08 14 | G 3/8 male   | crvena | 57,5        | 19      |
| K- 07 35 08 15 | G 1/4 female | crvena | 55,5        | 19      |
| K- 07 35 08 16 | G 3/8 female | crvena | 54,5        | 19      |