

# K-LKS 7,8 UWB

## Stems and plugs DN 7.8

### Osobine

Radni pritisak	0 - 35 bar, maximum static working pressure (non-pulsating)
Protok vazduha	1.800 l/min (at 6 bar and $\Delta p = 0.5$ bar)
Temperatura medija	-20 °C to +100 °C
Materijal	Mesing



### Napomena

Ostali podaci na upit.

### Artikal

Naziv	Definicija	Boja	SW (mm)
K- 07 35 02 71	Stem, I.D. 6	zelena	-
K- 07 35 02 72	Stem, I.D. 9	zelena	-
K- 07 35 02 73	Stem, I.D. 6	Brown	-
K- 07 35 02 74	Stem, I.D. 9	Brown	-
K- 07 35 02 75	Stem, I.D. 6	plava	-
K- 07 35 02 76	Stem, I.D. 9	plava	-
K- 07 35 02 77	Stem, I.D. 6	crvena	-
K- 07 35 02 78	Stem, I.D. 9	crvena	-
K- 07 35 02 79	Plug G 1/4 male	zelena	17
K- 07 35 02 80	Plug G 3/8 male	zelena	19
K- 07 35 02 81	Plug G 1/4 male	Brown	17
K- 07 35 02 82	Plug G 3/8 male	Brown	19
K- 07 35 02 83	Plug G 1/4 male	plava	17
K- 07 35 02 84	Plug G 3/8 male	plava	19
K- 07 35 02 85	Plug G 1/4 male	crvena	17
K- 07 35 02 86	Plug G 3/8 male	crvena	19