

K-GRUNDEJEKTION SBP-C ELK

Basic ejector »SBP-C« with blow-off valve and electronic vacuum switch, with integrated silencer

HANSA FLEX

Osobine

Osobine Vacuum generator with a single nozzle, available in six power ratings, with a high maximum vacuum value (85%)
Connection of compressed air and vacuum with push-in coupling
Basic housing with connection facility for a vacuum switch
Maximum suction capacity with minimum compressed air consumption
Minimum size, low weight
Various power ratings for optimised air consumption


Primena For universal use in handling systems with very high dynamic movements
Handling all kinds of air-tight components
For use in separation systems where space is restricted.
Construction of ejector blocks for centralised or decentralised individual control of suction pads.

Sistem dizni Brass

Priključak Push-in coupling

Prigušnik Plastic

Osnovno telo Impact-resistant plastic



Napomena

Ostali podaci na upit.

Opis

Purely pneumatic vacuum ejector that operates on the Venturi principle. Compressed air enters the ejector at A and flows through the nozzle B. This results in a vacuum immediately behind the nozzle outlet, and air is drawn in through the vacuum inlet D. This air and the driving air leave the ejector via the silencer C.

Artikal

| Naziv | Veličina dizne | Položaj mirovanja ventila za usisavanje | Priključak za komprimovani vazduh | Vakuumski priključak | Dimenzije |
|----------------|----------------|---|-----------------------------------|----------------------|---------------------|
| K- 07 45 01 20 | 1,0 | NO | 6 mm | 8 mm | 142mm x 15mm x 50mm |
| K- 07 45 01 22 | 1,5 | NO | 6 mm | 8 mm | 142mm x 15mm x 50mm |
| K- 07 45 01 24 | 2,0 | NO | 8 mm | 10 mm | 228mm x 20mm x 72mm |
| K- 07 45 01 26 | 2,5 | NO | 8 mm | 10 mm | 228mm x 20mm x 72mm |

Pribor

| | |
|--------------------------|-----------------------|
| K-ERSATZSCHALLDAEMPFER 1 | Replacement silencers |
| K-GRUNDPLATTEN 1 | Base plate |
| K-BEFESTIGUNGSSAETZE 1 | Mounting kit |