

# K-KOMPAKTEJEKTOREN CP SYST

Compact ejectors »CP«, system monitoring function: digital vacuum switch

**HANSA FLEX**


## Osobine

**Osobine** Vacuum generator with integrated control valves and system monitoring functions  
Gripping and blowing off can be controlled without the need for external valves  
Optimised air consumption thanks to many models with differing suction capacities  
Minimum energy costs in continuous operation thanks to automatic air-saving  
Easy adjustment with foil keypad and LED display of the settings

**Primena** Handling of air-tight or slightly porous workpieces in fully automated handling systems  
e.g. in the robotics, automotive, packaging, electronics, electrical engineering and metalworking industries

**Osnovno telo** Anodised aluminium

**Integrirano** NC blow-off valve, filter, silencer, non-return valve



## Napomena

Mini-sensor with housing and connection cable, analogue or digital output signal. Minimum size and low weight combined with high measuring accuracy. Ostali podaci na upit.

## Opis

Purely pneumatic vacuum ejector that operates on the Venturi principle. Compressed air enters the ejector at A and flows through the nozzle B. This results in a vacuum immediately behind the nozzle outlet, and air is drawn in through the vacuum inlet D. This air and the driving air leave the ejector via the silencer C.

## Dodatne informacije

Important: Order two connection plugs per ejector. A cable set is included with the compact ejector with automatic air-saving.

## Artikal

Naziv	Veličina dizne	Položaj mirovanja ventila za usisavanje	Priključak za komprimovani vazduh	Vakuumski priključak	Potrošnja vazduha usisa (L/min)	maks. sposobnost usisavanja (L/min)	Dimenzije	Radni pritisak (bar)
K- 07 45 01 35	1,5	NC	G 1/8 IG	G1/8 female	117,0	65,0	72mm x 20mm x 164mm	5,0
K- 07 45 01 36	1,5	NO	G 1/8 IG	G1/8 female	117,0	65,0	72mm x 20mm x 164mm	5,0
K- 07 45 01 39	2,0	NC	G 1/4 IG	G 3/8 female	190,0	116,0	113mm x 22mm x 168mm	6,0
K- 07 45 01 40	2,0	NO	G 1/4 IG	G 3/8 female	190,0	116,0	113mm x 22mm x 168mm	6,0
K- 07 45 01 43	2,5	NC	G 1/4 IG	G 3/8 female	310,0	161,0	113mm x 22mm x 183mm	6,0
K- 07 45 01 44	2,5	NO	G 1/4 IG	G 3/8 female	310,0	161,0	113mm x 22mm x 183mm	6,0

## Pribor

K-ANSCH KABEL VAKUUMSCHAL Connection cable for vacuum switch

K-ERSATZSCHALLDAEMPFER 2 Replacement silencers

K-ERSATZFILTERELEMENTE Replacement filter element