

K-KOMPAKTEJEKTOREN MINI

Mini-compact ejectors

HANSA FLEX

Osobine


Osobine	<p>Vacuum generator with integrated control valves and system monitoring functions</p> <p>Gripping and blowing off can be controlled without the need for external valves</p> <p>Optimised air consumption thanks to many models with differing suction capacities</p> <p>Minimum energy costs in continuous operation</p> <p>Easy adjustment with foil keypad, LED display of the settings</p> <p>Minimum size and low weight</p> <p>Optimum vacuum generation directly on the suction pad</p> <p>Complete solution for very simple installation</p> <p>Short learning curve thanks to "teach" function</p> <p>No need for additional sensors</p> <p>Easily visible status indication</p>
----------------	--

Primena	<p>Ideal where space is restricted and for highly dynamic movements, handling with industrial robots, linear axes</p> <p>pick-and-place systems</p>
----------------	---

Stepen evakuacije	85 %
--------------------------	------

Osnovno telo	Anodised aluminium
---------------------	--------------------

Integrirano	NC blow-off valve, filter, silencer, non-return valve
--------------------	---



Napomena

Mini-sensor with housing and connection cable, analogue or digital output signal. Minimum size and low weight combined with high measuring accuracy. Ostali podaci na upit.

Opis

Purely pneumatic vacuum generator that operates on the Venturi principle. Compressed air enters the ejector at A and flows through the nozzle B. This results in a vacuum immediately behind the nozzle outlet, and air is drawn in through the vacuum inlet D. This air and the driving air leave the ejector via the silencer C.

Dodatne informacije

Important: Order two connection plugs per ejector.

Artikal

Naziv	Veličina dizne	Položaj mirovanja ventila za usisavanje	Priključak za komprimovani vazduh	Vakuumski priključak	Potrošnja vazduha usisa (L/min)	maks. sposobnost usisavanja (L/min)	Dimenzije	Radni pritisak (bar)
K- 07 45 01 46	1,0	NC	M 5 IG	M5 female	46,0	23,0	65mm x 10mm x 107mm	4,5
K- 07 45 01 45	1,0	NO	M 5 IG	M5 female	46,0	23,0	65mm x 10mm x 107mm	4,5

Pribor

K-ANSCHLUSSSTECK MAGNETVE 1	Connection plug for solenoid valves
K-ERSATZSCHALLDAEMPFER	Replacement silencers
K-ERSATZFILTERELEMENTE 1	Replacement filter element