K-FEDERSTOESSEL
Spring plungers

Osobine

Primena	Handling of workpieces with differing heights (eg. Curved metal sheets) Handling of very sensitive workpieces, very soft landing is assured
Temperatura min.	0 °C
Temperatura max.	80 °C
Priključak usisivača	M 3 female
Verzija	Spring plunger with high-strength steel rodl, guide sleeve and lower damping spring Plunger rod with integrated vacuum guide
Putanja opruge	5,0 mm



Napomena
Ostali podaci na upit.

Opis
Suitable for all round or oval suction pads in our standard range.

Artikal

Naziv	Vakuumski priključak	Dužina (mm)	Vertikalno opterećenje (N/m2)
K- 07 45 00 73	M 3 female	33,5	550
K- 07 45 00 76	M 5 female	41,2	1500
K- 07 45 00 74	M 5 female	47,2	1500
K- 07 45 00 75	M 5 female	59,2	1500
K- 07 45 00 70	G 1/8 female	80,0	3700
K- 07 45 00 67	G 1/8 female	95,0	3700
K- 07 45 00 71	G 1/8 female	93,0	3700
K- 07 45 00 68	G 1/8 female	124,5	2400
K- 07 45 00 72	G 1/8 female	124,0	2400
K- 07 45 00 69	G 1/8 female	154,0	2400

Uprkos pažljivom proveravanju, ne možemo isključiti greške i ne preuzimamo nikakvu garanciju za navedene podatke.