

K-DRS MDR 3 M ENTLASTU VENT

»MDR 3« pressure switches, with unloading valve, on/off switch, motor protection circuit and flange F4 1/4

HANSA FLEX

Osobine

| | |
|------------------------------|------------------------------------|
| Temperatura medija | -5 °C to +80 °C |
| maks. pritisak isključivanja | 35 bar |
| Sposobnost komutacije | 7,5 kW |
| Vrsta kontakta | NC (3-pole) |
| maks. učestalost komutacije | 120 (electrical), 600 (mechanical) |
| Vrsta zaštite | IP 54 |



Napomena

Ostali podaci na upit.

Opis

Three-phase version

Artikal

| Naziv | Priključak za komprimovani vazduh | Opseg podešavanja | maks. opterećenje |
|----------------|-----------------------------------|-------------------|-------------------|
| K- 07 30 24 19 | G 1/2 | 4,0 - 11,0 bar | 10,0 - 16,0 A |
| K- 07 30 24 20 | G 1/2 | 4,0 - 11,0 bar | 4,0 - 6,3 A |
| K- 07 30 24 18 | G 1/2 | 4,0 - 11,0 bar | 6,3 - 10,0 A |
| K- 07 30 24 23 | G 1/2 | 6,0 - 16,0 bar | 4,0 - 6,3 A |
| K- 07 30 24 22 | G 1/2 | 6,0 - 16,0 bar | 6,3 - 10,0 A |