

K-DRS MDR 5 O ENTLASTU VENT

»MDR 5« pressure switches, without unloading valve / on/off switch / motor protection circuit, with flange 1/4

HANSA FLEX

Osobine

Temperatura medija	-5 °C to +80 °C
maks. pritisak isključivanja	16 bar
Sposobnost komutacije	5,5 kW
Vrsta kontakta	NC (3-pole)
maks. učestalost komutacije	120 (electrical), 600 (mechanical)
Vrsta zaštite	IP 54



Napomena

G thread acc. to DIN EN ISO 228-1, with ISO flange plate (acc. to ISO 5211)
Ostali podaci na upit.

Opis

Three-phase version

Napomene u vezi porudžbine

For use on devices that have to be vented whenever they are turned off, either because of safety regulations or for technical reasons. The pneumatic devices are disconnected from the system and simultaneously vented each time they are shut off.

Dodatne informacije

Important: A thermal, 3-pole overcurrent relay must be ordered together with these switches. Without this relay, the on/off mechanism does not work.

Artikal

Naziv	Priključak za komprimovani vazduh	Opseg podešavanja
K- 07 30 24 24	G 1/2	2,0 - 11,0 bar
K- 07 30 24 26	G 1/2	2,5 - 16,0 bar