

K-DRS WECHSELKONTAKT

Pressure switches, changeover type

HANSA FLEX

Osobine

| | |
|---------------------------------------|---|
| Konstrukcija | Spring-loaded diaphragm (NBR); Spring-loaded piston (10 to 70 bar versions) |
| Oblast primene | Air, hydraulic oil, oil emulsions, water |
| Temperatura okoline | -25 °C to +85 °C |
| Priključak na električnu mrežu | Tab connectors 3 x 6.3 x 0.8 |
| Učestalost komutacije | 200/min. |
| Napon komutacije | 42 V |
| Funkcija | Changeover |
| Materijal | Galvanised steel |



Napomena

Ostali podaci na upit.

Opis

For liquid, non-corrosive and gaseous media. Easy to adjust, even under pressure. Can be integrated in any mounting position. Pressure adjustment by means of a hexagon-head screw.

Artikal

| Naziv | Navoj | Opseg podešavanja | Materijal |
|----------------|-------|-------------------|------------------|
| K- 07 30 28 33 | G 1/4 | 0,3 - 2,0 bar | Galvanised steel |
| K- 07 30 28 34 | G 1/4 | 1,0 - 10,0 bar | Galvanised steel |
| K- 07 30 28 35 | G 1/4 | 10,0 - 70,0 bar | Galvanised steel |