

# K-DRS W BAJONETT

## Pressure switches - changeover type

### Osobine

Konstrukcija	Spring-loaded diaphragm (UR); Spring-loaded piston; (10 to 70 bar versions)
Temperatura okoline	-25 °C to +85 °C
Priključak na električnu mrežu	Bayonet coupling connector Ø 2.5 mm
Učestalost komutacije	200/min.
Merni napon	42 V
Funkcija	Changeover
Materijal	Galvanised steel



### Napomena

Ostali podaci na upit.

### Opis

Special pressure switches for critical (water) or outdoor applications. Maximum degree of protection IP67 when a bayonet coupling is used for the electrical connection.

### Artikal

Naziv	Navoj	Opseg podešavanja
K- 07 30 28 36	G 1/8	0,5 - 2,0 bar
K- 07 30 28 37	G 1/8	1,0 - 10,0 bar
K- 07 30 28 38	G 1/8	10,0 - 70,0 bar
K- 07 30 28 39	G 1/4	0,5 - 2,0 bar
K- 07 30 28 40	G 1/4	1,0 - 10,0 bar
K- 07 30 28 41	G 1/4	10,0 - 70,0 bar

### Pribor

K-WECHSELKONTAKT BANJOETT Changeover type bayonet coupling