


K-BKR MINI DREGRIF 1

Mini ball valves

HANSA FLEX

Osobine

| | |
|--------------------|---------------------|
| Radni pritisak | maks. 10 bara |
| Temperatura medija | -10 °C to +80 °C |
| Obrtna ručica | Plastic |
| Kučíšte i kugla | Nickel-plated brass |
| Zaptivka kugle | PTFE |
| Zaptivka vretena | NBR |



Napomena

Ostali podaci na upit.

Artikal

| Naziv | DN | Navoj | H (mm) | L (mm) | L1 (mm) | SW (mm) |
|----------------|----|----------------------------|-----------|-----------|------------|------------|
| K- 07 30 20 48 | 6 | Rp 1/8 female | 21,5 | 36,5 | 19,0 | 14 |
| K- 07 30 20 49 | 6 | Rp 1/4 female | 21,5 | 43,0 | 19,0 | 14 |
| K- 07 30 29 76 | 7 | Rp 3/8 female | 22,5 | 48,0 | 18,0 | 18 |
| K- 07 30 29 77 | 10 | Rp 1/2 female | 32,0 | 59,0 | 25,0 | 22 |
| K- 07 30 20 30 | 6 | R/Rp 1/8 male / 1/8 female | 21,5 | 35,5 | 19,0 | 14 |
| K- 07 30 20 31 | 6 | R/Rp 1/4 male / 1/8 female | 21,5 | 38,0 | 19,0 | 14 |
| K- 07 30 20 32 | 6 | R/Rp 1/4 male / 1/4 female | 21,5 | 40,5 | 19,0 | 14 |
| K- 07 30 20 33 | 6 | R/Rp 3/8 male / 1/4 female | 21,5 | 41,5 | 19,0 | 14 |
| K- 07 30 29 78 | 8 | R/Rp 3/8 male / 3/8 female | 22,5 | 44,5 | 19,5 | 18 |
| K- 07 30 29 79 | 10 | R/Rp 1/2 male / 1/2 female | 32,5 | 55,5 | 26,5 | 22 |