

# K-3 BKR T DOPPELWIRKEND T2

Stainless steel ball valves, 3-way, with double-acting actuator, T-bore, normal position

**HANSA FLEX**

## Osobine

|                              |  |
|------------------------------|--|
| Konstrukcija                 | Pneumatic actuators, in double- or single acting version, with integrated end-position feedback                                |
| Otvor                        | T oblik  |
| Radni pritisak               | max. 63 bar (depending on temperature and nominal size)  |
| Radna temperatura            | -20 °C to +70 °C   |
| Ugao obrtanja                | 90 °   |
| Standardizovani međusklopovi | Interface actuator / valve: four or eight threaded holes in the drive housing according to EN ISO 5211, Interface actuator / S |
| Upravljački pritisak         | 5.5 bar  |
| Adapter ventila              | Acc. to NAMUR  |
| Pogon                        | aluminium eloxed   |
| Zaptivka pogona              | NBR  |
| Kuglični ventil              | Stainless steel 1.4401, with ISO-flange plate  |
| Zaptivka kugličnog ventila   | PTFE/FKM   |



## Napomena

G thread acc. to DIN EN ISO 228-1, with ISO flange plate (acc. to ISO 5211)

Ostali podaci na upit.

## Opis

3-way cock, reduced bore

## Dodatne informacije

Other T-positions on request

## Artikal

| Naziv          | DN | Navoj    | Položaj | A<br>(mm) | B<br>(mm) | D<br>(mm) | L<br>(mm) | SW<br>(mm) |
|----------------|----|----------|---------|-----------|-----------|-----------|-----------|------------|
| K- 07 30 03 00 | 15 | Rp 1/2   | T 2     | 116,0     | 130,0     | 20,0      | 73,0      | 27         |
| K- 07 30 03 02 | 20 | Rp 3/4   | T 2     | 116,0     | 136,0     | 23,0      | 80,0      | 32         |
| K- 07 30 03 04 | 25 | Rp 1     | T 2     | 133,0     | 148,5     | 28,5      | 90,0      | 41         |
| K- 07 30 03 06 | 32 | Rp 1 1/4 | T 2     | 133,0     | 153,5     | 36,5      | 90,0      | 50         |
| K- 07 30 03 08 | 40 | Rp 1 1/2 | T 2     | 137,0     | 173,0     | 37,0      | 105,0     | 55         |
| K- 07 30 03 10 | 50 | Rp 2     | T 2     | 161,0     | 196,5     | 47,5      | 115,0     | 71         |