

K-MV G 230 V, 50 - 60 HZ D

Normally closed, 230 V, 50 to 60 Hz, directly operated

HANSA FLEX

Osobine

| | |
|--------------------------------|---|
| Priključak na električnu mrežu | For Pg 11P connector socket, acc. to DIN 4400 |
| Vrsta zaštite | IP65 (with connector socket fitted) |
| Temperatura medija | max. +90 °C with Perbunan-seal; max. +130 °C with FKM-Seal |
| Kučiče, sedište ventila | Stainless steel |
| Unutrašnji delovi | Stainless steel |
| Zaptivka | Perbunan (NBR) or FKM |



Napomena

Ostali podaci na upit.

Opis

Available versions, Directly operated, Combined operation

Artikal

| Naziv | Navoj | maks. radni pritisak (bar) | NW | Zaptivni materijal | A (mm) | B (mm) | Konstrukcija |
|----------------|-------|----------------------------|-----|--------------------|--------|--------|--------------|
| K- 07 30 22 46 | G 1/8 | 20 | 2,4 | NBR | 80,0 | 30,0 | 1 |
| K- 07 30 22 48 | G 1/8 | 20 | 2,4 | FKM | 80,0 | 30,0 | 1 |
| K- 07 30 22 47 | G 1/4 | 12 | 4,0 | NBR | 85,0 | 45,0 | 1 |
| K- 07 30 22 49 | G 1/4 | 12 | 4,0 | FKM | 85,0 | 45,0 | 1 |