


### Osobine

Diferencijalni pritisak	0 - 16 bar
Temperatura medija	-10 °C to +180 °C
Priklučak upravljačkog vazduha	G 1/8
Temperatura upravljačkog medija	max. +60 °C
Temperatura okoline	-20 °C to +70 °C
dozvoljeni staticki pritisak	Max. 16 bar
Kućište ventila	Stainless steel AISI 316
Spojni deo	Stainless steel
Upravljačka glava	Polyamide (glass fibre-reinforced)
Klipovi	Nickel-plated brass (DN 15 to DN 32), PBT + GF 30% (DN 40 to DN 50)
Vreteno	Stainless steel
Zaptivni materijal	PTFE



### Napomena

G thread acc. to DIN EN ISO 228-1, with ISO flange plate (acc. to ISO 5211)

For use on devices that have to be vented whenever they are turned off, either because of safety regulations or for technical reasons. The pneumatic devices are disconnected from the system and simultaneously vented each time they are shut off.

Ostali podaci na upit.

### Opis

Angle-seat valves with external pilot control and a self-aligning valve disc for neutral (bronze body) or corrosive (stainless steel body) media. Very high flow due to angled seat design. Water hammer prevented by fluid entry under the disc. Suitable for vacuum operation (low vacuum). NAMUR interface on the piston actuator. 3/2 and 5/2-way valves can be mounted directly.

### Dodatne informacije

Other versions e.g. for steam on request

Information on max. operating differential pressures apply for air, gas, corrosive aggressive media, water

### Artikal

Naziv	A (mm)	C (mm)	F (mm)	Navoj	maks. razlika u radnom pritisku (bar)	min. upravljački pritisak	maks. upravljački pritisak
K-07 30 25 33	190,0	169,0	85,0	G 1/2	16	4	10
K-07 30 25 34	195,0	176,0	95,0	G 3/4	10	4	10
K-07 30 25 35	213,0	195,0	95,0	G 3/4	16	4	10
K-07 30 25 36	219,0	202,0	105,0	G 1	11	4	10