

K-ABBLV VA 1

Stainless steel blow-off safety valves, G 1/8

HANSA FLEX

Osobine

| | |
|-------------------|------------------------|
| Radni pritisak | 0.5 - 60 bar |
| Radna temperatura | max. 180 °C |
| Zaptivke | FKM |
| Opruga | Stainless steel 1.4310 |
| Kučište | Stainless steel 1.4305 |



Napomena

G thread acc. to DIN EN ISO 228-1, with ISO flange plate (acc. to ISO 5211)

Ostali podaci na upit.

Opis

Manual adjustment of the blow-off pressure (lock nut).

Napomene u vezi porudžbine

For use on devices that have to be vented whenever they are turned off, either because of safety regulations or for technical reasons. The pneumatic devices are disconnected from the system and simultaneously vented each time they are shut off.

Dodatne informacije

These blow-off valves can also be supplied with a fixed setting and a TÜV type test number. Please ask for an offer.

Artikal

| Naziv | Navoj | Proradni pritisak | Kapacitet prodivavanja | C (mm) | D (mm) | do (mm) | SW (mm) |
|----------------|-------|-------------------|------------------------|-----------|-----------|------------|------------|
| K- 07 30 21 75 | G 1/8 | 0.5 - 1.0 bar | to 50 l/min | 27,0 | 7,0 | 3,0 | 16 |
| K- 07 30 21 76 | G 1/8 | 1.0 - 4.0 bar | to 200 l/min | 27,0 | 7,0 | 3,0 | 16 |
| K- 07 30 21 77 | G 1/8 | 3.0 - 7.0 bar | to 350 l/min | 27,0 | 7,0 | 3,0 | 16 |
| K- 07 30 21 78 | G 1/8 | 6.0 - 12.0 bar | to 650 l/min | 27,0 | 7,0 | 3,0 | 16 |
| K- 07 30 21 79 | G 1/8 | 10.0 - 18.0 bar | to 870 l/min | 27,0 | 7,0 | 3,0 | 16 |
| K- 07 30 21 80 | G 1/8 | 16.0 - 32.0 bar | to 1600 l/min | 27,0 | 7,0 | 3,0 | 16 |
| K- 07 30 21 81 | G 1/8 | 30.0 - 60.0 bar | to 3000 l/min | 27,0 | 7,0 | 3,0 | 16 |